

UPS2000-A Series

(1-3kVA)

Introduction

UPS2000-A series with a capacity ranging from 1kVA to 3kVA is an online double conversion power system that delivers continuous, high-quality AC Power. It's really a perfect power protection solution for small power scenarios.

Scenarios

- Small and medium enterprises, large enterprise branch offices, bank branches and other small data centers
- Networks, communications systems, automatic control systems and other precision equipment
- Family, office

Features

High Reliability

- Wide input voltage range to minimize battery use
- Online double conversion power system provides continuous, high-quality AC Power

Intelligent Management

- Variety of monitoring methods: supports SNMP / MODBUS / Dry contact / USB
- Supports function of delay shutdown: turning off the computer application systems and operating systems safely
- Multiple remote monitoring: supports SMS, E-mail, etc

High Availability

- LCD screen supports real-time monitoring and convenient operation
- Built-in battery, Easy to use
- Enables quick and easy configuration of the UPS



UPS2000-A-1K/2K/3K

Specifications

Rated capacity (kVA/kW)		1kVA/0.8kW	2kVA/1.6kW	3kVA/2.4kW	
Input: Output		1-in: 1-out			
Mains Input	Input wiring	L+N+PE			
	Rated voltage	220/230/240 VAC			
	Input voltage range	110-300 VAC			
	Input frequency range	40-70 Hz			
	Input power factor	0.99			
Bypass Input	Input rated voltage	220/230/240 VAC			
	Input voltage range	174-264 VAC			
	Input frequency range	47-53 Hz / 57-63Hz			
Battery	Battery voltage	Standard	24 VDC	48 VDC	72 VDC
		Long backup	36 VDC	72 VDC	96 VDC
	Backup time	Standard	> 5 minutes @ 80% load		
		Long backup	Depending on the capacity of external batteries		
Output	Output wiring	L+N+PE			
	Output connections	4 X IEC C13	6 X IEC C13	6 X IEC C13	
	Rated voltage	220/230/240 VAC ±1%			
	Output frequency	47-53 Hz or 57-63 Hz (Synchronized Range); 50/60Hz±0.5% (Battery Mode)			
	Output power factor	0.8			
	Waveform	Sinewave, THDv< 3%			
	System Efficiency	88%	89%	90%	
	Overload capacity	<110% overload for 10 minutes; <130% overload for 1 minute; ≥130% overload for 3 second			
Environment	Operating temperature	0 to 40°C			
	Storage temperature	-40 to +70°C (battery: -20 to +40°C)			
	Relative Humidity	0%–95% RH (no condensation)			
	Operating Altitude	0-1000 m. Above 1,000 m, derating 1% for each additional 100 m			
	Audible noise	<50dB @ 1 Meter			
Others	D x W x H (mm)	Standard	282 x 145 x 220	397 x 145 x 220	421 x 190 x 318
		Long backup	282 x 145 x 220	397 x 145 x 220	397 x 145 x 220
	Weight (kg)	Standard	9.2	16.8	27
		Long backup	4.1	6.7	7.4
	Certifications	EN/IEC 62040-1; EN/IEC 62040-2; EN/IEC 62040-3; CE; CB, etc			
	Communications	USB, RS232 (optional RS485/Dry contact)			

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808
Version No.: M3-022333-20150423-C-3.0
www.huawei.com